





HABERMANN AURUM
PUMPEN


APNO 8450

High Chrome Dewatering Pump

50 Hz



Weight : 530kg / 1168lbs



Shaft Speed : 2850rpm

Solid Passage : 20mm

Outlet : 200mm, 8in

OUTPUT	HEAD	FLOW
45 kW	Rated : 35m, 115ft	Rated : 75 l/s, 1188gpm
60 HP	Max : 55m, 180ft	Max : 96.6 l/s, 1531gpm

Pump Type	Electric Submersible Pumps	
	Three Phase	
	IP 68	
Motor	Type	Induction Motor
	Poles	2 Pole
	Insulation	Class F
	Protector	D.O.L. · Circle Thermal Protector Star-Delta · Miniature Thermal Protectors
	Starter Method	D.O.L. · Star-Delta
Lubricant		Food Grade (ISO VG32)
Impeller Type		Closed
Shaft Seal	Double Mechanical Seal	
	Silicon Carbide VS Ceramic / Carbon	
Bearings		C3 Shielded ball bearings
Cable	H07BQF	
	Length: 20m (66ft) or longer upon request.	
Materials	Pump Casing	Ductile Iron
	Impeller	Chromium Iron
	Motor Frame	Gray Iron
	Motor Shaft	Stainless Steel
	Outer Cover	Carbon Steel
	Strainer	Carbon Steel
Max. Liquid Temperature		40°C (104°F)
Max. Submersion Depth		20m (66ft)
pH Range		pH 5 - pH 8