



Technical Data Multi Grapple

Model												
	t	kg	t	l/min	bar	l/min	bar	sec	Breaker type	L	mm	mm
	(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)	(10)	(11)	(12)
MG 100	0,7 - 1,2	90	0,6	15	300	3 - 5	150 - 170	0,5	SB 52	30	600	310
MG 200	1 - 3	175	1,5	25	300	5 - 10	150 - 170	1	SB 152	50	900	450
MG 300	2 - 5	290	2	35	300	5 - 10	150 - 170	2	SB 152	110	1.170	500
MG 400	4 - 8	450	2,3	40	300	10 - 15	150 - 170	2	SB 302	210	1.565	600
MG 500	5 - 9	460	2,4	35 - 50	300	10 - 15	150 - 170	2,3	SB 302	250	1.565	700
MG 800	10 - 16	825	3,8	70 - 100	350	20 - 25	150 - 170	1,4	MB 1000	350	1.770	800
MG 1000	12 - 20	1150	4,6	85 - 120	350	20 - 25	150 - 170	2,2	MB 1700	500	1.900	800
MG 1500	17 - 28	1700	6,8	120 - 170	350	30 - 35	150 - 170	3,3	MB 1700	800	2.035	1.020
MG 1800	20 - 28	1800	6,8	150 - 170	350	30 - 35	150 - 170	3,1	MB 1700	860	2.035	1.200
MG 2300	25 - 38	2280	8,0	160 - 180	350	30 - 35	150 - 170	2,7	HB 2500	900	2.290	1.200
MG 2700	28 - 50	2750	9,0	180 - 200	350	30 - 35	150 - 170	4	HB 2500	920	2.270	1200
MG 3000	35 - 50	3250	9,0	180 - 200	350	30 - 35	190 - 210		HB 2500	1300	2.460	1.500
MG 5000	28 - 50	2750	9	180 - 200	350	50 - 60	190 - 210		HB 7000	1.000	3.000	1500

(1)Carrier weight class# (2)Service weight# (3)Force# (4)Oil flow rate# (5)Operating pressure# (6)Oil flow rate Rotation# (7)Operating pressure Rotation# (8)Cycles time (open/close)#

(9)Hole pattern Breaker type# (10)Capacity# (11)Jaw opening# (12)Grapple width